

GB

Page 1 of 13  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 23.05.2016 / 0009  
Replacing version dated / version: 28.01.2016 / 0008  
Valid from: 23.05.2016  
PDF print date: 23.05.2016  
Liquimate Kraftkleber 8050 MS 290 mL  
Art.: 6165

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Liquimate Kraftkleber 8050 MS 290 mL**  
**Art.: 6165**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture:**

Seam sealant  
Sector of use [SU]:  
SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites  
SU21 - Consumer uses: Private households (=general public = consumers)  
SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)  
Chemical product category [PC]:  
PC 1 - Adhesives, sealants  
Process category [PROC]:  
PROC 8a - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities  
PROC 8b - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities  
PROC 9 - Transfer of substance or preparation into small containers (dedicated filling line, including weighing)  
PROC10 - Roller application or brushing  
Article Categories [AC]:  
AC99 - Not required.  
Environmental Release Category [ERC]:  
ERC 4 - Industrial use of processing aids in processes and products, not becoming part of articles  
ERC 7 - Industrial use of substances in closed systems  
ERC 8a - Wide dispersive indoor use of processing aids in open systems  
ERC 8d - Wide dispersive outdoor use of processing aids in open systems

#### **Uses advised against:**

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

GB

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany  
Phone: (+49) 0731-1420-0, Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

**Emergency information services / official advisory body:**

---

**Telephone number of the company in case of emergencies:**

+49 (0) 700 / 24 112 112 (LMR)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) 1272/2008 (CLP)**

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

#### 2.2 Label elements

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 23.05.2016 / 0009  
 Replacing version dated / version: 28.01.2016 / 0008  
 Valid from: 23.05.2016  
 PDF print date: 23.05.2016  
 Liquimate Kraftkleber 8050 MS 290 mL  
 Art.: 6165

## Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH210-Safety data sheet available on request.

### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

## SECTION 3: Composition/information on ingredients

### 3.1 Substance

n.a.

### 3.2 Mixture

<b>trimethoxyvinylsilane</b>	
<b>Registration number (REACH)</b>	--
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	220-449-8
<b>CAS</b>	2768-02-7
<b>content %</b>	1-<3
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Flam. Liq. 3, H226 Acute Tox. 4, H332

<b>3-(trimethoxysilyl)propylamine</b>	
<b>Registration number (REACH)</b>	--
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	237-511-5
<b>CAS</b>	13822-56-5
<b>content %</b>	1-<3
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Skin Irrit. 2, H315 Eye Dam. 1, H318

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Do not induce vomiting. Consult doctor immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 23.05.2016 / 0009  
Replacing version dated / version: 28.01.2016 / 0008  
Valid from: 23.05.2016  
PDF print date: 23.05.2016  
Liquimate Kraftkleber 8050 MS 290 mL  
Art.: 6165

#### 4.3 Indication of any immediate medical attention and special treatment needed

n.c.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

##### Suitable extinguishing media

CO<sub>2</sub>

Extinction powder

Water jet spray

Large fire:

Water jet spray / alcohol resistant foam

##### Unsuitable extinguishing media

High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Oxides of sulphur

#### 5.3 Advice for firefighters

No special measures required.

Protective respirator with independent air supply.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

No special measures required.

#### 6.2 Environmental precautions

If leakage occurs, dam up.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

#### 6.3 Methods and material for containment and cleaning up

Pick up mechanically and dispose of according to Section 13.

Or:

Soak up with absorbent material (e.g. sand, earth) and dispose of according to Section 13.

#### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

### SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

#### 7.1 Precautions for safe handling

##### 7.1.1 General recommendations

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Ensure good ventilation.

Avoid contact with eyes or skin.

##### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### 7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

GB

Page 4 of 13  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 23.05.2016 / 0009  
 Replacing version dated / version: 28.01.2016 / 0008  
 Valid from: 23.05.2016  
 PDF print date: 23.05.2016  
 Liquimate Kraftkleber 8050 MS 290 mL  
 Art.: 6165

Store product closed and only in original packing.

### 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

The methanol listed below can arise upon contact with water.

Chemical Name	Carbon black		Content %:
WEL-TWA: 3,5 mg/m <sup>3</sup>	WEL-STEL: 7 mg/m <sup>3</sup>	---	
Monitoring procedures: ---			
BMGV: ---		Other information: ---	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

trimethoxyvinylsilane						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,34	mg/l	
	Environment - marine		PNEC	0,034	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	3,4	mg/l	
	Environment - sewage treatment plant		PNEC	110	mg/l	
	Environment - sediment, freshwater		PNEC	0,27	mg/kg	
	Environment - sediment, marine		PNEC	0,12	mg/kg	
	Environment - soil		PNEC	0,046	mg/kg	
Consumer	Human - dermal	Short term, systemic effects	DNEL	26,9	mg/kg bw/day	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	93,4	mg/m <sup>3</sup>	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,3	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1,04	mg/m <sup>3</sup>	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,3	mg/kg bw/day	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	0,69	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	4,9	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,69	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	4,9	mg/kg	

3-(trimethoxysilyl)propylamine						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note

Page 5 of 13  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 23.05.2016 / 0009  
 Replacing version dated / version: 28.01.2016 / 0008  
 Valid from: 23.05.2016  
 PDF print date: 23.05.2016  
 Liquimate Kraftkleber 8050 MS 290 mL  
 Art.: 6165

	Environment - freshwater		PNEC	0,33	mg/l	
	Environment - marine		PNEC	0,033	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	3,3	mg/l	
	Environment - sediment, freshwater		PNEC	1,2	mg/kg dry weight	
	Environment - sediment, marine		PNEC	0,12	mg/kg dry weight	
	Environment - soil		PNEC	0,045	mg/kg dry weight	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	17	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	5	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	5	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	58	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	8,3	mg/kg bw/d	

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.  
 Applies only if maximum permissible exposure values are listed here.

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

**Eye/face protection:**  
 With danger of contact with eyes.  
 Tight fitting protective goggles with side protection (EN 166).

**Skin protection - Hand protection:**  
 Protective PVC gloves (EN 374)  
 Protective PE/ EVAL/ PE gloves (EN 374)  
 Minimum layer thickness in mm:  
 >= 0,12  
 Permeation time (penetration time) in minutes:  
 > 480  
 The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.  
 The recommended maximum wearing time is 50% of breakthrough time.

**Skin protection - Other:**  
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

**Respiratory protection:**  
 Normally not necessary.

**Thermal hazards:**  
 Not applicable

Additional information on hand protection - No tests have been performed.  
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
 Selection of materials derived from glove manufacturer's indications.  
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

GB

Page 6 of 13  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 23.05.2016 / 0009  
 Replacing version dated / version: 28.01.2016 / 0008  
 Valid from: 23.05.2016  
 PDF print date: 23.05.2016  
 Liquimate Kraftkleber 8050 MS 290 mL  
 Art.: 6165

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Pastelike, Liquid
Colour:	Black
Odour:	Mild
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	>100 (DIN 53213 (Pensky-Martens, closed cup))
Evaporation rate:	n.a.
Flammability (solid, gas):	n.a.
Lower explosive limit:	n.a.
Upper explosive limit:	n.a.
Vapour pressure:	n.a.
Vapour density (air = 1):	n.a.
Density:	1,47 g/cm <sup>3</sup> (20°C, DIN 51757)
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	235 °C (Ignition temperature )
Auto-ignition temperature:	No
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	Product is not explosive.
Oxidising properties:	Not determined

### 9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	0 % (Organic solvents )

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

None known

### 10.4 Conditions to avoid

None known

### 10.5 Incompatible materials

None known

### 10.6 Hazardous decomposition products

See also Subsection 10.1 to 10.5.

See also section 5.2

## SECTION 11: Toxicological information

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.05.2016 / 0009

Replacing version dated / version: 28.01.2016 / 0008

Valid from: 23.05.2016

PDF print date: 23.05.2016

Liquimate Kraftkleber 8050 MS 290 mL

Art.: 6165

## 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Liquimate Kraftkleber 8050 MS 290 mL						
Art.: 6165						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value, Vapours
Acute toxicity, by inhalation:	ATE	>5	mg/l/4h			calculated value, Dust
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:					OECD 437 (Bovine Corneal Opacity + Permeability Test for Identif. Ocular Corros. + Severe Irritants)	Not irritant
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

trimethoxyvinylsilane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	7120	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	3540	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LD50	2773	ppm/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Acute toxicity, by inhalation:	LC50	16,8	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Slightly irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising
Germ cell mutagenicity:						Negative
Carcinogenicity:						Negative
Reproductive toxicity:						Negative
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	10	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development. Tox. Screening Test)	Vapours
Symptoms:						drowsiness, dizziness, nausea, abdominal pain, breathing difficulties, visual disturbances

3-(trimethoxysilyl)propylamine						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	





GB

Page 9 of 13  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 23.05.2016 / 0009  
 Replacing version dated / version: 28.01.2016 / 0008  
 Valid from: 23.05.2016  
 PDF print date: 23.05.2016  
 Liquimate Kraftkleber 8050 MS 290 mL  
 Art.: 6165

12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.

<b>trimethoxyvinylsilane</b>							
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Time</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
12.1. Toxicity to fish:	LC50	96h	>=100	mg/l	Brachydanio rerio		
12.1. Toxicity to fish:	LC50	96h	191	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	168,7	mg/l	Daphnia magna	Regulation (EC) 440/2008 C.2 (DAPHNIA SP. ACUTE IMMOBILISATION TEST)	
12.1. Toxicity to algae:	EC50	72h	>957	mg/l	Scenedesmus subspicatus		
12.1. Toxicity to algae:	IC50	72h	>100	mg/l	Selenastrum capricornutum		
12.1. Toxicity to algae:	NOEC/NOEL	72h	>957	mg/l	Scenedesmus subspicatus		88/302/EC
12.2. Persistence and degradability:		28d				OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50		>2500	mg/l	activated sludge		

<b>3-(trimethoxysilyl)propylamine</b>							
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Time</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
12.1. Toxicity to fish:	LC50	96h	>934	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	331	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	EC50	72h	>1000	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	67	%		OECD 301 A (Ready Biodegradability - DOC Die-Away Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	67	%		Regulation (EC) 440/2008 C.4-A (DETERMINATION OF 'READY' BIODEGRADABILITY - DOC DIE-AWAY TEST)	Not readily biodegradable, Analogous conclusion
12.3. Bioaccumulative potential:							No
12.4. Mobility in soil:							Slight
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50		3400	mg/l	activated sludge		

GB

Page 10 of 13  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 23.05.2016 / 0009  
 Replacing version dated / version: 28.01.2016 / 0008  
 Valid from: 23.05.2016  
 PDF print date: 23.05.2016  
 Liquimate Kraftkleber 8050 MS 290 mL  
 Art.: 6165

Toxicity to bacteria:	EC50		43	mg/l	Pseudomonas putida		Analogous conclusion5,75 h
Toxicity to bacteria:	EC10		13	mg/l	Pseudomonas putida		Analogous conclusion5,75 h

Carbon black							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	24h	>5600	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	NOEC/NO EL	3d	10000	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:							Not biodegradable, Insoluble
12.3. Bioaccumulative potential:							Not to be expected
Toxicity to bacteria:	EC0	3h	>=800	mg/l	activated sludge	Regulation (EC) 440/2008 C.22 (SOIL MICROORGANISMS - CARBON TRANSFORMATION TEST)	

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

#### For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Untampered packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

## SECTION 14: Transport information

### General statements

14.1. UN number: n.a.

#### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Classification code: n.a.

LQ (ADR 2015): n.a.

GB

Page 11 of 13  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 23.05.2016 / 0009  
 Replacing version dated / version: 28.01.2016 / 0008  
 Valid from: 23.05.2016  
 PDF print date: 23.05.2016  
 Liquimate Kraftkleber 8050 MS 290 mL  
 Art.: 6165

14.5. Environmental hazards: Not applicable  
 Tunnel restriction code:

### Transport by sea (IMDG-code)

14.2. UN proper shipping name:  
 14.3. Transport hazard class(es): n.a.  
 14.4. Packing group: n.a.  
 Marine Pollutant: n.a.  
 14.5. Environmental hazards: Not applicable

### Transport by air (IATA)

14.2. UN proper shipping name:  
 14.3. Transport hazard class(es): n.a.  
 14.4. Packing group: n.a.  
 14.5. Environmental hazards: Not applicable

### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

For classification and labelling see Section 2.

Observe restrictions:

General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC): n.a.

### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

Revised sections: 3, 4, 5, 6, 7, 8, 10, 11, 12, 13, 14, 15, 16

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

Flam. Liq. — Flammable liquid

Acute Tox. — Acute toxicity - inhalation

Skin Irrit. — Skin irritation

Eye Dam. — Serious eye damage

## Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds

Page 12 of 13  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 23.05.2016 / 0009  
 Replacing version dated / version: 28.01.2016 / 0008  
 Valid from: 23.05.2016  
 PDF print date: 23.05.2016  
 Liquimate Kraftkleber 8050 MS 290 mL  
 Art.: 6165

approx. approximately  
 Art., Art. no. Article number  
 ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)  
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)  
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
 BCF Bioconcentration factor  
 BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)  
 BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)  
 BMGV Biological monitoring guidance value (EH40, UK)  
 BOD Biochemical oxygen demand  
 BSEF Bromine Science and Environmental Forum  
 bw body weight  
 CAS Chemical Abstracts Service  
 CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids  
 CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques  
 CIPAC Collaborative International Pesticides Analytical Council  
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)  
 CMR carcinogenic, mutagenic, reproductive toxic  
 COD Chemical oxygen demand  
 CTFA Cosmetic, Toiletry, and Fragrance Association  
 DMEL Derived Minimum Effect Level  
 DNEL Derived No Effect Level  
 DOC Dissolved organic carbon  
 DT50 Dwell Time - 50% reduction of start concentration  
 DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)  
 dw dry weight  
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance  
 EC European Community  
 ECHA European Chemicals Agency  
 EEA European Economic Area  
 EEC European Economic Community  
 EINECS European Inventory of Existing Commercial Chemical Substances  
 ELINCS European List of Notified Chemical Substances  
 EN European Norms  
 EPA United States Environmental Protection Agency (United States of America)  
 ERC Environmental Release Categories  
 ES Exposure scenario  
 etc. et cetera  
 EU European Union  
 EWC European Waste Catalogue  
 Fax. Fax number  
 gen. general  
 GHS Globally Harmonized System of Classification and Labelling of Chemicals  
 GWP Global warming potential  
 HET-CAM Hen's Egg Test - Chorionallantoic Membrane  
 HGWP Halocarbon Global Warming Potential  
 IARC International Agency for Research on Cancer  
 IATA International Air Transport Association  
 IBC Intermediate Bulk Container  
 IBC (Code) International Bulk Chemical (Code)  
 IC Inhibitory concentration  
 IMDG-code International Maritime Code for Dangerous Goods  
 incl. including, inclusive  
 IUCLID International Uniform Chemical Information Database  
 LC lethal concentration  
 LC50 lethal concentration 50 percent kill  
 LCLo lowest published lethal concentration  
 LD Lethal Dose of a chemical  
 LD50 Lethal Dose, 50% kill  
 LDLo Lethal Dose Low  
 LOAEL Lowest Observed Adverse Effect Level  
 LOEC Lowest Observed Effect Concentration  
 LOEL Lowest Observed Effect Level

Page 13 of 13  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 23.05.2016 / 0009  
Replacing version dated / version: 28.01.2016 / 0008  
Valid from: 23.05.2016  
PDF print date: 23.05.2016  
Liquimate Kraftkleber 8050 MS 290 mL  
Art.: 6165

LQ Limited Quantities  
MARPOL International Convention for the Prevention of Marine Pollution from Ships  
n.a. not applicable  
n.av. not available  
n.c. not checked  
n.d.a. no data available  
NIOSH National Institute of Occupational Safety and Health (United States of America)  
NOAEC No Observed Adverse Effective Concentration  
NOAEL No Observed Adverse Effect Level  
NOEC No Observed Effect Concentration  
NOEL No Observed Effect Level  
ODP Ozone Depletion Potential  
OECD Organisation for Economic Co-operation and Development  
org. organic  
PAH polycyclic aromatic hydrocarbon  
PBT persistent, bioaccumulative and toxic  
PC Chemical product category  
PE Polyethylene  
PNEC Predicted No Effect Concentration  
POCP Photochemical ozone creation potential  
ppm parts per million  
PROC Process category  
PTFE Polytetrafluorethylene  
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
SADT Self-Accelerating Decomposition Temperature  
SAR Structure Activity Relationship  
SU Sector of use  
SVHC Substances of Very High Concern  
Tel. Telephone  
ThOD Theoretical oxygen demand  
TOC Total organic carbon  
TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)  
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods  
VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))  
VOC Volatile organic compounds  
vPvB very persistent and very bioaccumulative  
WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).  
WHO World Health Organization  
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.